








TECH SPECS

RIMS ROAD & TOURING

	RR 415	RR 465 double	RR 585	R 450	R 520	TK 540	TK 540 disc
ETRTO	622 x 15	622 x 15	622 x 15	622 x 15	622 x 15	622 x 19	622 x 19
ERD	599mm	599mm	582mm	596mm	584mm	600mm	600mm
Width/Largeur/Breite	19.4mm	19.4mm	19.5mm	19,8mm	20.1mm	23.6mm	23.6mm
Height/Hauteur/Höhe	20.8mm	20.8mm	30.3mm	22,5mm	29.5mm	20.2mm	20.2mm
Number of holes Nombre de trous Lochzahl	28, 32	28, 32	20, 24, 28, 32	28, 32	28, 32	32, 36	32
Valve hole ø Perçage de valve ø Ventilloch ø	6.5mm	6.5mm	6.5mm	6.5mm	6.5mm	6.5mm	6.5mm
Weight ± 5% Poids ± 5% Gewicht ± 5%	415g	465g	585g	450g	530g	540g	540g
Eyelets/Oeillets/Ösen	single	double	none	none	none	double	double
Intended use Utilisation Einsatzbereich	 Light		 Aero				
Recommended spoke Rayon recommandé Empfohlene Speiche	7	1, 5, 7	2, 5, 6	2, 5, 6	2, 5, 6	3, 5	3, 5
Spoke tension max. Tension de rayon max. Speichenspannung max.	1100 N	1200 N	1200 N	1200 N	1200 N	1200 N	1200 N
Rim tape Fonds de jante Felgenband	622 x 16mm	622 x 16mm	622 x 16mm	622 x 16mm	622 x 16mm	622 x 19mm	622 x 19mm
Tire dimension min. Dimension de pneu min. Reifendimension min.	700 x 19C	700 x 19C	700 x 19C	700 x 19C	700 x 19C	700 x 1" C	700 x 1" C
Tire dimension max. Dimension de pneu max. Reifendimension max.	700 x 25C	700 x 25C	700 x 25C	700 x 25C	700 x 25C	700 x 2.35" C	700 x 2.35" C
Tire pressure max.* Pression de pneu max.* Reifendruck max.*	9 bar	9 bar	9 bar	9 bar	9 bar	6 bar	6 bar
Riders weight max. Poids d'utilisateur max. Fahrergewicht max.	90 kg	110 kg	110 kg	100 kg	110 kg	130 kg	130 kg

* or like posted on the tire