

TECH SPECS WHEELS MTB

Model	Width	Weight	Rim												Hub															
			ETRTO	Clincher	Tubular	Tubeless	Tubeless kit	Valve holes 6.5 mm	Valve holes 8.5 mm	Material		Rim color				Hub axle system						Free wheel		Rotor body system		Disc mount		Hub color		
										Carbon	Aluminium	Black	White	Grey	Carbon	Quick release 5 mm	9 mm DT Swiss Thru bolt	Lefty	10 mm DT Swiss Thru bolt	12 mm DT Swiss Thru axle	X-12	Bolt on	15 mm	20 mm	DT Swiss ratchet system®	Two pawl system	Shimano 9 / 10 and Sram 9 / 10 / 11		Campagnolo 9 / 10 / 11	Center lock®
XM 1550 Tricon® black	100	721	559 x 19.5	●	●	●	●	●	●	●	●	●	○	●														●		black/gun metal
XM 1550 Tricon® black	100	730	559 x 19.5	●	●	●	●	●	●	●	●	●	○	○														●		black/gun metal
XM 1550 Tricon® black	lefty	715	559 x 19.5	●	●	●	●	●	●	●	●	●			●													●		black/gun metal
XM 1550 Tricon® black	135	856	559 x 19.5	●	●	●	●	●	●	●	●	●	○			●	○	○						●			●		●	black/gun metal
XM 1550 Tricon® black	142	850	559 x 19.5	●	●	●	●	●	●	●	●	●	○			○	○	●						●			●		●	black/gun metal
XM 1550 Tricon® white	100	721	559 x 19.5	●	●	●	●	●	●	●	●	●	○	●														●		white/gun metal
XM 1550 Tricon® white	100	730	559 x 19.5	●	●	●	●	●	●	●	●	●	○	○														●		white/gun metal
XM 1550 Tricon® white	135	856	559 x 19.5	●	●	●	●	●	●	●	●	●	○			●	○	○						●			●		●	white/gun metal
XM 1550 Tricon® white	142	850	559 x 19.5	●	●	●	●	●	●	●	●	●	○			○	○	●						●			●		●	white/gun metal
XM 1550 Tricon® 29	100	836	622 x 19.5	●	●	●	●	●	●	●	●	●	○	●														●		black/gun metal
XM 1550 Tricon® 29	100	845	622 x 19.5	●	●	●	●	●	●	●	●	●	○	○														●		black/gun metal
XM 1550 Tricon® 29	lefty	830	622 x 19.5	●	●	●	●	●	●	●	●	●			●													●		black/gun metal
XM 1550 Tricon® 29	135	970	622 x 19.5	●	●	●	●	●	●	●	●	●	○			●	○	○										●		black/gun metal
M 1700 Tricon® aluminium	100	800	559 x 19.5	●	●	●	●	●	●	●	●	●	○															●		grey
M 1700 Tricon® aluminium	100	780	559 x 19.5	●	●	●	●	●	●	●	●	●	○															●		grey
M 1700 Tricon® aluminium	135	900	559 x 19.5	●	●	●	●	●	●	●	●	●	○			○	○	○										●		grey
M 1700 Tricon® black	100	800	559 x 19.5	●	●	●	●	●	●	●	●	●	○															●		black
M 1700 Tricon® black	100	780	559 x 19.5	●	●	●	●	●	●	●	●	●	○															●		black
M 1700 Tricon® black	135	900	559 x 19.5	●	●	●	●	●	●	●	●	●	○			○	○	○										●		black

● = Serie ○ = Option

*Weight without cl adapter or quick release or thru axle

TECH SPECS WHEELS MTB

No. of spokes	Spokes						Nipples				Technical data						Accessories										
	Spoke typ		Length				Spoke color	Nipple typ				Nipple color	Lacing	Intended use	Rim tape	Tire dimension min.	Tire dimension max.	Axle clamping force (min./max.) 4000N/8000N	Maximum tire pressure [bar]	Recommended riders weight max. [kg]	RWS Ratchet wheelmounting system	Rim tape	Wheel bag	Quick release	Centering tools	Center lock® adapter	
	Left	Right	Left cross mm	Left radial mm	Right cross mm	Right radial mm		DT Pro lock® torx	DT Pro lock® hexagonal aluminium	DT Pro lock® brass	DT Pro lock® hidden																
24	DT aerolite	DT aerolite	256	247	258	248	white	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT aerolite	256	247	258	248	white	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT aerolite	255	244	257	248	white	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT new aero	257	248	255	243	white	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT new aero	257	248	255	243	white	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT aerolite	256	247	258	248	black	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT aerolite	256	247	258	248	black	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT new aero	257	248	255	243	black	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT aerolite	DT new aero	257	248	255	243	black	●				black	open crowfoot	XM	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
30	DT aerolite	DT aerolite	284	277	286	280	white	●				black	open crowfoot	XM	22 x 622	29" x 1.7"	29" x 2.4"	●	4	100	●	●					●
30	DT aerolite	DT aerolite	284	277	286	280	white	●				black	open crowfoot	XM	22 x 622	29" x 1.7"	29" x 2.4"	●	4	100	●	●					●
30	DT aerolite	DT aerolite	281	274	285	279	white	●				black	open crowfoot	XM	22 x 622	29" x 1.7"	29" x 2.4"	●	4	100	●	●					●
30	DT aerolite	DT new aero	286	279	283	274	white	●				black	open crowfoot	XM	22 x 622	29" x 1.7"	29" x 2.4"	●	4	100	●	●					●
24	DT new aero	DT new aero	256	247	258	249	black	●				black	open crowfoot	M	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT new aero	DT new aero	256	247	258	249	black	●				black	open crowfoot	M	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT new aero	DT new aero	257	249	255	244	black	●				black	open crowfoot	M	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT new aero	DT new aero	256	247	258	249	black	●				black	open crowfoot	M	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT new aero	DT new aero	256	247	258	249	black	●				black	open crowfoot	M	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●
24	DT new aero	DT new aero	257	249	255	244	black	●				black	open crowfoot	M	22 x 559	26" x 1.7"	26" x 2.4"	●	4	100	●	●					●

● = Serie ○ = Option

TECH SPECS WHEELS MTB

Model	Width	Weight	Rim												Hub														
			ETRTO	Clincher	Tubular	Tubeless	Tubeless kit	Valve holes 6.5 mm	Valve holes 8.5 mm	Material		Rim color			Hub axle system						Free wheel		Rotor body system		Disc mount		Hub color		
										Carbon	Aluminium	Black	White	Grey	Carbon	Quick release 5 mm	9 mm DT Swiss Thru bolt	Lefty	10 mm DT Swiss Thru bolt	12 mm DT Swiss Thru axle	X-12	Bolt on	15 mm	20 mm	DT Swiss ratchet system®	Two pawl system		Shimano 9 / 10 and Sram 9 / 10	Campagnolo 9 / 10 / 11
FX 1950 Tricon®	100	965	559 x 23	●	●	●	●	●	●	●	●	●	○	○							●	○					●	●	green
FX 1950 Tricon®	110	965	559 x 23	●	●	●	●	●	●	●	●	●	○	○							○	●					●	●	green
FX 1950 Tricon®	135	1035	559 x 23	●	●	●	●	●	●	●	●	●	○		●	○	○				●	○			●	●	●	●	green
FX 1950 Tricon®	142	1035	559 x 23	●	●	●	●	●	●	●	●	●	○		○	○	●				●	○			●	●	●	●	green
FX 1950 Tricon®	150	1060	559 x 23	●	●	●	●	●	●	●	●	●	○								●	○			●	●	●	●	green
XRC 950T	100	510	571 x 26		●			●	●				●	●	○												●		black/carbon
XRC 950T	135	610	571 x 26		●			●	●				●	●		○					●				●	●	●		black/carbon
XRC 950T 29	100	580	633 x 26		●			●	●				●	●	○												●		black/carbon
XRC 950T 29	135	680	633 x 26		●			●	●				●	●		○					●				●	●	●		black/carbon
XRC 1150	100	550	559 x 17	●				●	●		●		●	○													●		white/carbon
XRC 1150	135	650	559 x 17	●				●	●		●		●		○						●				●	●	●		white/carbon
XRC 1350	100	590	559 x 17	●				●	●				●	●	○												●		black
XRC 1350	100	585	559 x 17	●				●	●				●	○	○						●						●		black
XRC 1350	135	710	559 x 17	●				●	●				●	●		○	○	○			●				●	●	●		black
XR 1450	100	660	559 x 18	●			○	●		●			●	○													●		white
XR 1450	100	660	559 x 18	●			○	●		●			○	○							●						●		white
XR 1450	135	800	559 x 18	●			○	●		●			●			○	○	○			●				●	●	●		white

● = Serie ○ = Option

*Weight without cl adapter or quick release or thru axle

TECH SPECS WHEELS MTB

No. of spokes	Spokes						Nipples				Technical data							Accessories										
	Spoke typ		Length				Spoke color	Nipple typ				Nipple color	Lacing	Intended use	Rim tape	Tire dimension min.	Tire dimension max.	Axle clamping force (min./max.) 4000N/8000N	Maximum tire pressure [bar]	Recommended riders weight max. [kg]	RWS Ratchet wheelmounting system	Rim tape	Wheel bag	Quick release	Centering tools	Center lock® adapter		
	Left	Right	Left cross mm	Left radial mm	Right cross mm	Right radial mm		DT Pro lock® torx	DT Pro lock® hexagonal aluminium	DT Pro lock® brass	DT Pro lock® hidden																	
30	DT aero comp	DT aero comp	251	243	252	244	white	●				black	open crowfoot	FR	25 x 559	26" x 1.9"	26" x 2.7"	●	3	130		●						
30	DT aero comp	DT aero comp	251	243	252	244	white	●				black	open crowfoot	FR	25 x 559	26" x 1.9"	26" x 2.7"	●	3	130		●						
30	DT aero comp	DT aero comp	253	245	252	244	white	●				black	open crowfoot	FR	25 x 559	26" x 1.9"	26" x 2.7"	●	3	130	●	●						
30	DT aero comp	DT aero comp	253	245	252	244	white	●				black	open crowfoot	FR	25 x 559	26" x 1.9"	26" x 2.7"	●	3	130		●						
30	DT aero comp	DT aero comp	253	245	253	245	white	●				black	open crowfoot	FR	25 x 559	26" x 1.9"	26" x 2.7"	●	3	130		●						
28	DT aerolite	DT aerolite	257		260		white		●			black	3-cross	X	–	26" x 1.95"	26" x 2.2"	●	4	90	●		●				●	
28	DT aerolite	DT aerolite	257		255		white		●			black	3-cross	X	–	26" x 1.95"	26" x 2.2"	●	4	90	●		●		●		●	
32	DT aerolite	DT aerolite	284		286		white		●			black	3-cross	X	–	29" x 1.95"	29" x 2.2"	●	4	90	●		●				●	
32	DT aerolite	DT aerolite	284		282		white		●			black	3-cross	X	–	29" x 1.95"	29" x 2.2"	●	4	90	●		●		●		●	
24	DT aerolite	DT aerolite	262		265		black		●			black	2-cross	X	22 x 559	26" x 1.5"	26" x 2.1"	●	3	90	●	●	●				●	
24	DT aerolite	DT aerolite	263		260		black		●			black	2-cross	X	22 x 559	26" x 1.5"	26" x 2.1"	●	3	90	●	●	●		●		●	
28	DT aerolite	DT aerolite	267		268		black		●			black	3-cross	X	22 x 559	26" x 1.5"	26" x 2.1"	●	3	90	●	●	●				●	
28	DT aerolite	DT aerolite	267		268		black		●			black	3-cross	X	22 x 559	26" x 1.5"	26" x 2.1"		3	90		●	●				●	
28	DT aerolite	DT aerolite	268		266		black		●			black	3-cross	X	22 x 559	26" x 1.5"	26" x 2.1"	●	3	90	●	●	●		●		●	
28	DT aerolite	DT aerolite	268		270		black		●			red	3-cross	XR	22 x 559	26" x 1.5"	26" x 2.25"	●	4	90	●	●					●	
28	DT aerolite	DT aerolite	268		270		black		●			red	3-cross	XR	22 x 559	26" x 1.5"	26" x 2.25"	●	4	90		●					●	
28	DT aerolite	DT aerolite	270		268		black		●			red	3-cross	XR	22 x 559	26" x 1.5"	26" x 2.25"	●	4	90	●	●					●	

● = Serie ○ = Option